



Martini dECO QUIET

Engineered for premium sound absorption. Available as a board or a decorative panel with a fabric finish.

csmartini.com.au



CSR Martini Pty Limited
P.O. Box 560, Ingleburn NSW 1890
martinienquiries@csr.com.au
1300 767 776





Application

Interior wall and ceiling panelling, workstation partitions and pin boards. Used in spaces such as offices, meeting rooms, theatres, restaurants, libraries, classrooms, sports halls and lecture theatres.

Environmental Benefits and Credentials

- GreenTag^{Cert}™ certified
- Environmental Product Declaration (EPD)
Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Declare certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Volatile organic compounds (VOCs) generated in the manufacturing process is classified as low (0.01 mg/m³)s
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential



Size/Thickness

Thickness: 25/50mm

Standard panel size: 2420 x 1210mm and 2720 x 1210mm

Finish/Colour

Available on either a black or white base, finished on one side with Martini Captivate or Embrace fabric. Also available without fabric – dECO Quiet Board.

Fire Resistance

Test Standard	AS ISO 9705 – 2003	ISO 9705:1993
Building Code	NCC C1.10	NZBC C/VM2
Classification	Group 1 SMOGRA < 100m ² /s ²	Group 1-S Smoke Prod Rate < 5m ² / ²

Acoustic Performance

Frequencies	125hz	250hz	500hz	1,000hz	2,000hz	4,000hz	NRC
25 mm	0.10	0.50	0.85	1.00	1.00	1.00	0.85
50 mm	0.35	0.80	1.00	1.00	1.00	1.00	1.00

Tested to AS/ISO 354:2006.

For more information on dECO QUIET refer to the data sheet available for download on our website;
<http://www.csrmartini.com.au/downloads>

